

Rieju MRT 125cc Supermoto

	MRT 125 SM LC	Marathon 125 SM Pro
Brand / Type	4t - 125c.c. 4 Valves INJECTION	Minarelli 4T 125cc Variable Timing
Diam x Stroke	58 x 47 mm.	52 x 58,6 mm
Gear Change	6 Speed Manual	
Cooling	Liquid Cooled	
Carburator	Injection	
Start-up	Electric	
Chassis	Highly Resistant Double Cradle Steel Perimeter. Detachable Rear Sub-chassis.	
Front Suspension	Fork of Ø37mm.	R16v Inverted Fork of Ø40mm.
Rear Suspension	Mono-shock Shock absorber	Gas Mono-shock Shock absorber and Seaprate Bottle Prs* System
Front Tyre	100/80-17"	
Rear Tyre	130/70-17"	
Front Brake	Disc of Ø260mm.	Galfer Wave Disc of Ø300mm. With Double Piston Caliper
Rear Brake	Disc of Ø200mm	Galfer Wave Disc of Ø200mm
Distance Between axes	1.405 mm.	1.380 mm.
Length	2.148 mm.	2.070 mm.
Max. Height	1.165 mm.	1.145 mm.
Max. Width	800 mm.	
Seat Height	870 mm.	
Dry Weight	112 Kg.	121 Kg.
Petrol Tank	6,32 L	
Oil Tank	NA	
Indicators	Yes	
Temp. indicator	Yes	
Min. Oil indicator	NA	Yes
P.M. indicator	Yes	
Dashboard Digital	Yes	
Skid Plate	NA	
Handguard	Optional	Yes
Exhaust	Racing Muffler	Inox
Handlebars	Cross	Aluminium